HAMEIDA

Diesel Pump Calibration Oil

Test oil for diesel injection pump and injector test benches.



18 L

Drum — the only pack size

Net weight 14.5 kg per drum

Product facts

Product name	HAMEIDA Diesel Pump Calibration Oil
Application	Calibration / test oil for diesel injection pump and injector test benches
Reference standard	GB/T 8029 (Chinese national standard for diesel injection pump calibration oil)
Composition basis	White mineral oil + hydrotreated light distillate, with antioxidant, rust inhibitor and antifoam additives
Packaging	18 L drum only (net 14.5 kg)
Origin	Made in China — factory in Xingtai, Hebei

Certificates & Documents

✔ **MSDS** — available

✔ **Transport certificate:** non-dangerous goods (sea transport identification report) — non-DG under IMDG

HAMEIDA · WhatsApp +86 176 2401 2016 · sales@hameda.net

Typical properties

Property	Typical value
Density at 20°C	0.82 g/cm³
Kinematic viscosity at 40°C	2.70 mm²/s
Flash point (closed cup)	108°C
Distillation — initial boiling point	160°C
Distillation — 95% recovered	360°C
Distillation — final boiling point	375°C

Typical values, not a specification.

Certificates & Documents

✔ **MSDS** — available

✔ **Transport certificate:** non-dangerous goods (sea transport identification report)

Factory stock



Contact us on WhatsApp or by email for quotations and documents.

Sun, HAMEIDA
WhatsApp +86 176 2401 2016 · sales@hameda.net